



## **NEFA® HYB TINT XKV**

Colour Concentrates/Tints for Colouring Hybrid Sealant Systems and Special Applications

**Product description:**

NEFA® HYB TINT XKV are colour concentrates/Tints that are specially formulated for colouring hybrid sealant systems, are well tolerated and easy to incorporate and can be dosed. They are based on a phthalate-free plasticiser and can therefore be used in a wide range of systems. Optimum dispersion of the pigments ensures a high colour yield and reproducibility of the colour shades. The colour range consists of 12 standard shades and customer-specific shades.

**Material base:**

phthalate-free plasticiser, FDA-compliant

**Colours:**

Standard range NEFA® HYB TINT XKV	Density [g/cm <sup>3</sup> ]
NEFA HYB TINT XKV Black 7	1,03
NEFA HYB TINT XKV Blue 15:3	1,03
NEFA HYB TINT XKV Green 7	1,07
NEFA HYB TINT XKV Magenta 122	1,03
NEFA HYB TINT XKV Orange 67	1,04
NEFA HYB TINT XKV Red 101	2,00
NEFA HYB TINT XKV Red 170	1,04
NEFA HYB TINT XKV Violet 19	1,03
NEFA HYB TINT XKV White 6	2,00
NEFA HYB TINT XKV Yellow 184	1,47
NEFA HYB TINT XKV Yellow 42	1,06
NEFA HYB TINT XKV Yellow 74	1,75

**Properties:**

NEFA® HYB TINT XKV are miscible and compatible with each other. They are finely ground, flowable and very suitable for precise machine dosing.

**Application:**

NEFA® HYB TINT XKV must be homogeneously incorporated into the respective system using standard methods. When used in automatic dosing systems with agitator, the colour concentrates are very easy to dose. The colour concentrates must be homogenised before use. A compatibility test with the target system must be carried out before use. If you have any further questions regarding processing and handling, our technical staff will be happy to advise and support you.

**Viscosity:**

**2,000-10,000 mPa-s**, varies depending on colour shade

**Dosage:**

To be determined by your own tests.

**Storage:**

24 months in undamaged, sealed original container in a cool, frost-free storage location.

**Packaging unit:**

10 kg sheet metal hobbock, other container sizes on request

**Hazard information and safety advice:**

Users are requested to take the relevant data from the safety data sheet.

**Technical service and production site:**

Caparol Industrial Solutions GmbH, Neichener Straße 38, 04668 Grimma  
Phone +49 (0) 34382 704-0

Version: June 2025

This technical information has been compiled based on the state of the art and our experience. In view of the large number of possible requirements and conditions it is however still your responsibility as purchaser/user to check that our product/products are actually suitable for the planned application. If you still have queries about our product (e.g. about uses which are not listed in this technical information or about application), please contact us, we would be pleased to respond. Only the latest version of the Technical Information is valid. If necessary, please make sure this version is valid with an appropriate enquiry to us.