

NEFA® POX

Dyeing pastes for colouring 2-component epoxy resin coatings

Product description:

NEFA® POX dyeing pastes are specially matched, high concentration dyeing pastes based on A/F resin for incorporation in 2-component epoxy resin systems. NEFA® POX dyeing pastes are manufactured in existing (e.g. approx. RAL) or customer-specific colours for the coloration of transparent or filled epoxy coatings. A compatibility test should be carried out for applications in already pigmented epoxy systems. A high colour yield and reproducibility of the colours are ensured due to optimum dispersion of the pigments.

Material base:

A/F epoxy resin

Colours:

Colours / Colour deviations due to printing are possible.

**Properties:**

High opacity; no nuancing is necessary, colours are easy to incorporate as they are already adjusted (list of colours on request).

Application:

NEFA® POX dyeing pastes are incorporated homogeneously into Component A with usual methods. Opened containers should be closed carefully and used up quickly.

Density:

Approx. 1.4 to 2.5 g/cm³ depending on the colour

Dosage:

Transparent base: 2 – 4 % by weight referred to the mixture
Filled base: 4 – 8 % by weight referred to the mixture

Storage:

Storable for at maximum 24 months in undamaged, closed, original containers in a cool, frost-free place.

Packaging unit:

Hobbock (PE, sheet metal) 25 - 30 kg each,
other container sizes on request

Hazard information and safety advice:

Users are requested to take the relevant data from the safety data sheet

Technical service and production site:

Caparol Industrial Solutions GmbH, Neichener Strasse 38, 04668 Grimma
Phone +49 (0) 34382 704-0, Fax: +49 (0) 34382 704-16

version: 01/2020

This technical information has been compiled based on the state of the art and our experience. In view of the large number of possible requirements and conditions it is however still your responsibility as purchaser/user to check that our product/products are actually suitable for the planned application. If you still have queries about our product (e.g. about uses which are not listed in this technical information or about application), please contact us, we would be pleased to respond. Only the latest version of the Technical Information is valid. If necessary, please make sure this version is valid with an appropriate enquiry to us.