

## NEFA® TINT W

### Colour concentrates/tints for colouring aqueous systems

#### Product description:

NEFA® TINT W colour concentrates/tints are specially matched for the coloration of aqueous coating systems such as dispersion paints, aqueous epoxy resin systems or aqueous 2-component PU enamels. NEFA® TINT W colour concentrates/tints are free of binders and solvents and are manufactured in 15 standard colours for the coloration and nuancing of transparent or filled aqueous coating systems. A compatibility test should be carried out for applications in already pigmented systems. A high colour yield and reproducibility of the colours are ensured due to optimum dispersion of the pigments.

#### Material base:

Cross-linking and dispersion agents

#### Colours:

NEFA® TINT W standard range	Density [g/cm <sup>3</sup> ]	Approx. pigment content [%]
NEFA® TINT W BLACK 11	2,15	68
NEFA® TINT W BLACK 7	1,20	36
NEFA® TINT W BLUE 15:1, 15:3	1,36	26
NEFA® TINT W GREEN 17	2,02	63
NEFA® TINT W GREEN 7	1,49	27
NEFA® TINT W ORANGE 43	1,13	27
NEFA® TINT W RED 101	1,93	59
NEFA® TINT W RED 122	1,10	29
NEFA® TINT W RED 254	1,18	37
NEFA® TINT W VIOLET 23	1,35	16
NEFA® TINT W WHITE 6	2,04	69
NEFA® TINT W YELLOW 42	1,79	57
NEFA® TINT W YELLOW 74	1,18	48
NEFA® TINT W YELLOW 184	1,74	51

#### Properties:

NEFA® TINT W colour concentrates/tints are intermiscible and compatible.  
NEFA® TINT W colour concentrates/tints can be dosed by machine.

#### Application:

NEFA® TINT W colour concentrates/tints are homogeneously incorporated into the coating material (in Component A depending on the system) with the usual methods. Opened containers should be closed carefully and used up as soon as possible. The pastes must be homogenised before use.

#### Viscosity:

from 100 – 4500 mPas, varies according to colour

#### Dosage:

To be determined by the user's own tests.

#### Storage:

Storable for at maximum 1 year in undamaged, closed, original containers in a cool, frost-free place.

#### Packaging unit:

Hobbock (metal, enamelled inside), approx. 15 – 20 kg depending on colour, other container sizes on request

#### Hazard information and safety advice:

Users are requested to take the relevant data from the safety data sheet

#### Technical service and production site:

Caparol Industrial Solutions GmbH, Neichener Strasse 38, 04668 Grimma  
Phone +49 (0) 34382 704-0, Fax: +49 (0) 34382 704-16

Version: 01/2020

This technical information has been compiled based on the state of the art and our experience. In view of the large number of possible requirements and conditions it is however still your responsibility as purchaser/user to check that our product/products are actually suitable for the planned application. If you still have queries about our product (e.g. about uses which are not listed in this technical information or about application), please contact us, we would be pleased to respond. Only the latest version of the Technical Information is valid. If necessary, please make sure this version is valid with an appropriate enquiry to us.